

## Performance & Feature Reference



<b>Model Number</b>	GBL 10	N27921 (Truck Unloading Auger)	GBU 10
<b>Operating Weight</b>	4080 pounds	4540 pounds	5760 pounds
<b>Operating Dimensions</b>			
<b>Length</b>	170 in.	362 in. / w GBL	255 in.
<b>Width</b>	150 in.	290 in.	269 in.
<b>Height</b>	129 in.	129 in.	209 in.
<b>Storage/Travel Dimensions</b>			
<b>Length</b>	170 in.	362 in. / w GBL	263 in.
<b>Width</b>	150 in.	150 in.	103 in.
<b>Height</b>	130 in.	130 in.	107 in.
<b>Width</b>	(136 in with travel kit)		
<b>Hopper Dimensions</b>			
<b>GL-10 Loader</b>	100 in. X 104 in.		
<b>GL-10 Truck Auger</b>		40 in. X 72 in. X 12 in.	
<b>GL-10 Truck Auger w/extension</b>		40 in. X 72 in. X 19 in.	
<b>PTO</b>			
<b>RPM</b>	540	1000	540
<b>Horsepower</b>	50	120	50
<b>Shaft Size / Type</b>	6-B Spline	1 3/8 or 1 3/4	6-B Spline
<b>PTO Driveline Type</b>	Walterscheid W2400	Walterscheid W2400	Walterscheid W2400
<b>Hydraulics</b>			
<b>GPM (required)</b>	6	6	6
<b>PSI (required)</b>	2,000	2,000	2,000
<b>Connector Type</b>	Quick Couplers	Quick Couplers	Quick Couplers
<b>Auger Sizes</b>			
<b>Primary Auger</b>	17 in. / 385 RPM	13 in. / 540 RPM	
<b>Discharge Auger</b>			17 in. /331 RPM
<b>Cross Auger</b>			10 in. /356 RPM
<b>Secondary Auger</b>		14 in. / 540 RPM	Optional 5 in. Auxiliary
<b>Twin Hopper Auger</b>		7 In. /750RPM	
<b>Wheels / Tires</b>			
<b>Wheel Size</b>	33 in.	15 in.	31 in.
<b>Tire Size</b>	12.5L-15	16-6.5	11L-15
<b>Tire Type</b>	SureGrip Traction	Foam Filled Traction Tire	Implement
<b>Operational Braking System</b>	Hydraulic Disc		
<b>Performance</b>			
<b>Transfer Capacity</b>	26,000 Bushels / Hr.	11,900 Bushels / Hr.	8,500 Bushels / Hr.
<b>Bag Handling Capacity</b>			
<b>Diameter</b>	10 Foot Bags		9 foot or 10 Foot Bags
<b>Max. Length</b>	300 Feet		300 Feet